

Mark Super S • SV

Increased comfort for this compact, versatile powerhouse

- Motorized cutter head movement and hand-wheel for exact positioning of head
- Digital depth indicator for quill travel
- Tapping unit with adjustable rotation reversal for thread cutting
- Hardened gear racks and shafts for quiet operation and long life
- **More power and variable speed control for a wider range of applications**



- **Extensive standard equipment**
- **Automatic quill feed**
- **Large travel with TV 1000 table feed**
- **Multi-function position indicator**

Standard Equipment

3-axis position indicator, automatic quill feed, base, table feed TV 1000, drill chuck 13 mm, tool-holder bits, operator manual

Options

Part No.

• Clamping Tool Set Deluxe 14/M12	105295
• Mounting Shaft MT 4	108641
• Electronic Edge Tracer	129055

For additional options for this machine, visit our website and search for Mark Super S (Product Search)



Head swivels $\pm 45^\circ$

Specifications

		Mark Super S	Mark Super SV
Table dimensions	mm	800x240	800x240
Drilling capacity in steel	mm	32	25
Travel X-axis manual / autom.	mm	560 / 480	560 / 480
Travel Y-axis	mm	190	190
Spindle mount		MT 4	MK 4
Speed	1/min	(12) 75-3200	(2) 75-438 / 438-2500
Main motor rating	kW	1,5 / 1,1	1,5
Weight	kg	380	480
Part No.		301498	301490

SBF 40

Universal machine for milling and drilling

- Large compound sliding table with automatic infinitely variable feed on X-axis for coordinate drilling and light milling work
- manual drill feed can be switched to high-precision feed via a hand-wheel
- controllable automatic feed with 3 gear steps
- adjustable height of gear head and table



Infinitely variable milling table feed



Automatic quill feed with 3-step gears



Options	Part No.
• Accessory-Set MT 4 8-pc.	104594
• ER 32 Collet Set 6 pcs.	106052
• Mounting Shaft MT 4	108641

For additional options for this machine, visit our website and search for SBF (Product Search)

Specifications

		SBF 40
Table set up area	mm	730x210
Quill stroke	mm	120
Spindle nose-to-table surface distance	mm	600
Spindle nose-to-foot distance	mm	1.180
Drilling capacity in steel / ST37	mm	40
Speed range	1/min	(12) 75 - 3.200
Spindle mount		MT 4
Motor rating main drive	kW	1,5
Main drive, continuous load	kW	1,1
Overall dimensions (length x width x height)	m	0,83x0,76x1,85
Weight	kg	390
Part No.		101573

Standard Equipment

tapping unit, table feed TV 1000, draw bar, drill chuck, tool-holder bits, coolant system, operator manual